



CWC®SMART EP BONDING AGENT

Solvent Free Epoxy Resin Based Thixotropic Bonding Agent

CWC®SMART EP BONDING AGENT is a two component solvent Indicative Characteristics free thixotropic epoxy resin bonding system for joining old concrete to new concrete and old concrete to old concrete

Pack -A: Resin (white), Pack -B: Hardener (black) CWC®SMART EP BONDING AGENT conforms to ASTM C 881 Grade 3 Type II.

Advantages

- Provides a permanent bond
- Cures in both dry and damp conditions.
- Thixotropic can be applied on vertical and overhead surfaces without sagging
- Can be used as bonding agent for mortars, renders, stone, steel, iron etc.
- Easy to mix and apply
- Excellent adhesion to most building material

Domains of Application

It is mainly used to bond permanently freshly mixed concrete or mortar, glazed bricks, tiles, steel or other structural material to old sound concrete. It is based on a 100% epoxy formulation and contains no solvents or water diluents CWC®SMART EP **BONDING AGENT** is a time tested dimensionally stable compound, which has been extensively used for structural bonding.

Method of Application Surface Preparation

Surface should be clean, free from dirt, loose particles, oil, grease or other foreign material. Deep contaminated concrete or metal should be thoroughly cleaned by wire brush. Ensure that the surface is not too wet during application of Bonding Agent.

Appearance of cured film	Grey
Specific Gravity at 27°C	1.8 ±0.1
Solid content, % (w/w)	>98
Mixing Ratio, Pack –A:B (by	2:1
wt.)	
Pot life, minutes at 27°C,	> 45
100 g mass	
Application Temperature,	5 to 40
°C	
Coverage (Theoretical)	0.3-0.8 kg /m² per coat
	depending surface profile
Initial cure at 27°C, for	After 24 hours
pedestrian traffic	
Slant- Shear Bond Strength,	12 (minimum) or concrete
at 14 days, N/mm ²	failure
Compressive Strength, 14	> 60
days, MPa	
	t e e e e e e e e e e e e e e e e e e e

Mixing

A suitable power driven mixer / stirrer is recommended for uniform mixing of CWC®SMART EP BONDING AGENT. Stir the base and hardener separately. Add hardener into the base and stir well till a uniform color is achieved. Wait for 5 minutes for induction. Remix the mass again before apply it. All packs are preweighed and ready for on site mixing. Do not use fraction of any pack. Always use whole packs for best results.







CWC®SMART EP BONDING AGENT

Solvent Free Epoxy Resin Based Thixotropic Bonding Agent

Application

Apply a thin layer of SMART EP BONDING AGENT with brush or squeeze to the existing surface, working well into the substrate. Place fresh concrete/mortar while it is still tacky (2-5 hours). A second coat of **CWC®SMART EP BONDING AGENT** may be applied after the first thin layer of the applied SMART EP BONDING AGENT passes its tacky stage, prior to placing the freshly mixed concrete or mortar. Good concrete practice should be followed in placing, consolidation and curing of concrete. While application, the substrate temperature should be at least 5°C but not above 40°C.

Shelf Life & Storage

12 months from the date of manufacturing when stored in unopened, original sealed and dry condition at a temperature range from $+5^{\circ}\text{C}$ to 40°C

Packing

6 kg kit (Resin Part A – 4 kg, Hardener Part B – 2 kg)

Precautions

- Store the material at the 5° to 40°C temperature range in shaded cool place and keep it away from fire and any heated body. Clean all tools with MEK or any standard solvent before polymerization starts.
- Mix only sufficient materials for immediate requirements. Leave the mixed material to stand for 5-8 minutes to enable entrapped air, if any, to escape from the mix and then use as quickly as possible.
- Thixotropy or anti sagging property is greatly influenced with surface temperature.

Safety

- Wear hand gloves, safety shoes and safety goggles while using and handling the product.
- In case eyes or mouth are affected wash with plenty of clean water and seek medical treatment immediately.

Before use, refer to the Material Safety Data Sheet. The MSDS is available on www.cwcchemical.in

Regional Offices:

Mumbai:

Office No - 616/617, J K Chambers Sec-17, Vashi, Navi Mumbai-400703 Maharashtra, INDIA. 091 9920791030

Chennai:

Plot No.3/86-E, Ground Floor
AIEMA Road, Ambattur Industrial Estate
Chennai – 600058 Tamil Nadu, India
091 8939820144
www.cwcchemicals.com
info@cwcchemicals.com

