

Concrete Works Construction Chemicals Private Limited



CWC[®]PompEase 100

Concrete Pump Primer and Pumping Aid

Description

CWC®PompEase 100 is uniquely formulated to provide the concrete pumper with a cost effective replacement for premium priced grout, primer slurries or bagged cement primers. **CWC®PompEase 100** contains no bentonite, cementitious materials, soaps or air entraining agents.

Indicative characteristics

- Form : White Granular Powder
- Chemical base : Anionic Polymer
- Consumption : 100 gm will able to prime 60 meter of 5 inch pipe line.
- pH (1% soln.) : ≥ 6
- Chloride Content : Nil, as per BS 5075 (Part-I)
- Compatibility : All cements

ADVANTAGES :

CWC®PompEase 100 functions as a concrete pumping aid by creating thin lubrication film inside the pump and pipelines and reduce line pressure which enables the placement of hard to pump mixes and increasing the range of pump ability. Key advantages are:

- No need for expensive ready mixed priming grout.
- Eliminates the need for carrying bagged cement.
- Packaged in easy to carry and handle to use.
- Reduce friction and line pressure thereby increasing ease of pumping.
- Decrease wear on costly equipment.
- Reduces risk of blockage
- Decreases horsepower required for pumping
- Environmentally safe product

Domains of application

- All cement types
- All conventional concrete materials
- Ready mix concrete

Precautions

Not to be stored at high temperatures for long periods. Should be protected from frost. It is Non-toxic and formulated from chemicals which present no fire or health hazards. Spillages should be washed down immediately with water.

Method of use

Dosage: Each 100 gm **CWC®PompEase 100** to be mixed with 30 liters of water either in drum or in the hopper of the concrete pump. Mix the **CWC®PompEase 100** and water for approximately 2 minutes or until the mixture assumes a slick oily texture condition. Add this mixture into the pump ahead of the concrete. Details are in the below.

Pack (100gm	Water (liter)	Pipe Length
1 = 100gm	30	40 -60 meters
2 = 200gm	60	80 – 120 meters

Guideline Followed :

CWC®PompEase 100 will have no deleterious effects on the structural integrity of the concrete. Remember, as with any pump priming material, the first few quantity of concrete will have higher water content than the mix behind, which may affect certain pours such as slabs and columns. To avoid potential problems discard the first few quantity.

Shelf Life: If stored in unopened containers at normal ambient temperatures, a shelf-life of approximately 18 months.

Packaging

• 100gm / 200 gm Sachet

Safety

Before use, refer to the Material Safety Data Sheet. The MSDS is available on www.cwcchemicals.com.



Concrete Work Construction Chemicals Private Limited CIN: U74999PN2021PTC199740 Office No. 70, Mahavir Center, Fourth Floor, Sector 17, Vashi, Navi Mumbai 400703 Registered Office :- 1471 D.B. House, Office No. F - 4, 4th Floor, Madhavnagar Road, Madhavnagar Road-EWSD Sangli Maharashtra 416416 INDIA info@cwcchemicals.com, www.cwcchemicals.com

